

ELECTRIC CHARGER AC



**H1 22W** 

- > SMART
- > COMPACT
- > POWERFUL

Weight 9-10 Kg (with cable) 6-7 kg (with socket)

### **TECHNICAL SPECIFICATIONS**

#### **POWER SPECIFICATION**

AC Input	Input Rating	Three Phase: 3P+N+PE; 380~415VAC
	AC Input Connection	L1/L2/L3/N/PE
	Input Current	32A
	Frequency	50Hz / 60Hz
AC Output	Output Current	32A / 16A
	Output Power	22kW

### **USER INTERFACE & CONTROL**

Display	LED Pilot Lamp (standard) 5-inch LCD (optional)
User Authentication	RFID (ISO / IEC 14443A/B, ISO/IEC 15693, FeliCa™, Mifare), ISO 15118
Meter	Meter IC (Accuracy <1%) MID Meter (Optional)

#### **ENVIRONMENT**

Operating Temperature	-30° to + 50°C (standard) or -20°C to +50°C (w/ payment system
Humidity	< 85 % (RH) @50 °C
Altitude	≤ 2000m
IP/IK Level	IP56 IK08
Cooling Method	Natural Cooling

#### **COMMUNICATION**

Evtornal	AN + WiFi (standard) or AN+4G+WiFi (optional)
Internal (t	OCPP 1.6 JSON upgradeable to 2.0) EBUS (support in 2022)

#### **PROTECTION**

RCD/CCID	RCD Type A + DC 6mA
Input Side	UVP, OVP, Surge protection, Ground fault
Output Side	OCP & Control Pilot fault, Residual current protection
Protocol	OTP, Relay welding detection, CCID self-test MCU function fault detection

# **MECHANICAL**

Dimension (WxDxH)	291 x 139 x 500 mm
Weight	9-10 Kg (with cable) 6-7 kg (with socket)
Cable Length	5m

#### **REGULATION**

Certificate	IEC 61851-1 IEC 61851-21-2
Safety	CE
Charging Interface	IEC 62196-2 Type 2 Plug or Shuttered Socket
Wireless Certificate	RED

## hellonext.world info@hellonext.world

© 2023 Petrotec Group | All rights reserved. Petrotec, Hellonext, the Petrotec logo, the Hellonext logo and combinations thereof are registered trademarks of Petrotec Group. Other names are informational and may be trademarks of their respective owners. Hellonext is continuously improving its products. Changes on the specifications may occur without prior notice. The imagery used may be indicative of style only. The available brochures are a guide and do not constitute an offer or contract.

